






321G PN16 Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut No.-SIZE mm	Certificate
			L mm/in	X mm/in	Y mm/in	Z mm/in		
25 1	33.7 1.327	300 2.0	60.5 2.382	115 4.53	85 3.35	16 0.63	4-M12	UL FM VdS LPCB
32 1¼	42.4 1.669	300 2.0	60.5 2.382	140 5.51	100 3.94	16 0.63	4-M16	UL FM VdS LPCB
40 1½	48.3 1.902	300 2.0	60.5 2.382	150 5.91	110 4.33	16 0.63	4-M16	UL FM VdS LPCB
50 2	60.3 2.375	500 3.45	65 2.559	165 6.50	125 4.92	16 0.63	4-M16	UL FM VdS LPCB
65 2½	73.0 2.875	500 3.45	65 2.559	165 6.50	145 5.70	16 0.63	4-M16	UL FM
65 76.1	76.1 3.000	500 3.45	65 2.559	185 7.28	145 5.70	16 0.63	4-M16	UL FM VdS LPCB
80 3	88.9 3.500	500 3.45	65 2.559	200 7.87	160 6.30	16 0.63	8-M16	UL FM VdS LPCB
100 108.0	108.0 4.250	300 2.0	70 2.756	220 8.66	180 7.09	16 0.63	8-M16	UL FM
100 4	114.3 4.500	300 2.0	70 2.756	220 8.66	180 7.09	16 0.63	8-M16	UL FM VdS LPCB
125 133.0	133 5.250	300 2.0	70 2.756	250 9.84	210 8.27	18 0.71	8-M16	UL FM
125 139.7	139.7 5.500	300 2.0	70 2.756	250 9.84	210 8.27	18 0.71	8-M16	UL FM VdS LPCB
150 159.1	159.0 6.250	500 3.45	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM
150 165.1	165.1 6.500	500 3.45	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM LPCB
150 6	168.3 6.625	500 3.45	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM VdS LPCB
200 8	219.1 8.625	300 2.0	80 3.150	340 13.39	295 11.61	19 0.75	12-M20	UL FM VdS LPCB
250 10	273.0 10.750	300 2.0	85 3.346	405 15.94	355 13.98	21 0.83	12-M24	UL FM VdS
300 12	323.9 12.750	225 1.6	90 3.543	460 18.11	410 16.14	24 0.94	12-M24	UL FM VdS
350 14	377.0 14.843	225 1.6	100 3.937	520 20.47	470 18.50	25 1.00	16-M24	UL FM
400 16	426.0 16.772	225 1.6	110 4.331	580 22.83	525 20.67	27 1.06	16-M27	UL FM
450 18	480 18.897	225 1.6	115 4.528	640 25.196	585 23.03	20 0.787	20-M27	—

321GH PN25 Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut No.-SIZE mm	Certificate
			L mm/in	X mm/in	Y mm/in	Z mm/in		
100 108.0	108.0 4.250	362 2.5	70 2.756	230 9.05	190 7.48	18 0.71	8-M20	UL FM
100 4	114.3 4.500	362 2.5	70 2.756	235 9.25	190 7.48	16 0.63	8-M20	UL FM
150 159.0	159.0 6.250	362 2.5	70 2.756	300 11.80	250 9.85	20 0.79	8-M24	UL FM
150 165.1	165.1 6.500	362 2.5	70 2.756	300 11.80	250 9.84	18 0.71	8-M24	UL FM
200 8	219.1 8.625	362 2.5	80 3.150	360 14.17	310 12.20	19 0.75	12-M24	UL FM
250 10	273.0 10.75	362 2.5	85 3.346	425 16.73	370 14.57	22 0.87	12-M27	—
300 12	323.9 12.750	362 2.5	88 3.46	485 19.09	430 16.93	23.5 0.93	16-M27	—
350 14	355.6 12.750	362 2.5	100 3.94	555 21.85	490 19.29	26 1.02	16-M30	—
400 16	406.4 16.000	362 2.5	110 4.33	620 24.41	550 21.65	28 1.10	16-M33	—